





# **Printer Specifications**

Printer	
Print Area:	Edge-to-Edge/ Ribbon Saver
Resolution:	300dpi
Monochrome:	5 Sec./ Card (Up to 720 Cards/ Hour)
YMCKO:	22 Sec./ Card
Input Hopper:	100 Cards
Output Hopper:	40 Cards
Card Feeding:	Automatic Front Load/ Unload with Single By- Pass Slot
Memory:	64MB RAM
Display:	2 Line LCD
Control Panel:	2 LED Buttons
Supported Platforms:	Microsoft Windows 2000/ 2003/ XP/ Vista/ 7/ 8, Mac OS, Linux, AS/400, Open Card Format
Communication:	Ethernet/ USB
Power Supply:	AC110.220V, 50~60Hz
Power Consumption:	(MAX) 48W

## Media

Print Type:	Monochrome - Up to 2,600 Cards/ Roll
Card Size:	ISO CR-80 (54mm x 86mm/ 2.12" x 3.38")
Card Thickness:	0.38mm (15mil)~ 1.0mm (40mil)
Card Type:	PVC, PET, Composite PVC

### Printer Options

Magnetic:	ISO 7811 (Track I, II, III Read/Write),
	HiCo/LoCo,JIS II
Contact:	ISO 7816 (ID-1)
Contactless:	MIFARE, ISO 14443 (Type A/B), ISO 15693, DESFIRE, iCLASS
Printer Additions:	Flipper, Laminator

#### Dimensions

(W x L x H) Inch:	6.7 x 16.5 x 7.7
Weight (lbs)	10 lbs



#### Monochrome Ribbons

K W MG
Black White Metallic Gold



MS Metallic Sliver

**Authorized Dealer** 



810 Busch Ct. Columbus, OH 43229 (614) 840-9971